THIRD-ORDER LEVELING SEA LEVEL DATUM OF 1929 38-085-21 NEW CASTLE QUADRANGLE 187 KENTUCKY N3815-W8500/15 DIAGRAM NJ 16-6 LOUISVILLE


# UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Henry and Shelby Counties Final adjustment of 1973 Edition of 4/17/73

Only the permanent marks are listed for lines run more than 25 years before edition date

PR: DSW/dt

CARROLLTON (201 KY.-30 IND.)



LA GRANGE (188)

#### NGS VERTICAL CONTROL DATA

A. Quadrangle 380852

# INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.		PAGE NO.
849 903 912 TT STA NO 2 T 1926 7 TT STA NO 18 T 1926 TT STA NO 19 T 1926 TT STA NO 20 T 1926 TT STA NO 21 T 1926 TT STA NO 22 T 1926 TT STA NO 23 T 1926 TT STA NO 24 T 1926 TT STA NO 25 T 1925 TT STA NO 26 T 1926	3 3 3 3 5 5 766 5,9,12 3 3 335 4,7,8 330 11	72 RHP 1952 796 86 RHP 1952 895 87 RHP 1952 851 89 RHP 1952 815 90 RHP 1952 532 91 RHP 1952 489 92 RHP 1952 480 93 RHP 1952 542 TT 1 TWC 1952 545 TT 2 TWC 1952 492  NGS	10 10 11 12,13 12 12 12 12 12
TT STA NO 26 T 1926 TT STA NO 27 T 1926 8 TT STA NO 28 T 1926 TT STA NO 29 T 1926 C 1 1928 C 2 1928 46 FL 1950 858 TT TT 8 HF 1951 903 41 RHP 1952 817 63 RHP 1952 809 64 RHP 1952 844 66 RHP 1952 843 67 RHP 1952 835 68 RHP 1952 800 69 RHP 1952 868 71 RHP 1952 850	35 4,7,8 330 11 4 393 8 4 4 4,13 7,13666888 9910	T 31 1934 G 146 1949 EMINENCE 1935 GILTNER 1935 GILTNER 1935 (Az. mk.) GILTNER NO 1 1935 GILTNER NO 2 1935 CAMPBELL NO 1 1949 CAMPBELL NO 2 1949 DEFOE NO 1 1949 DEFOE NO 2 1949 DELLVILLE 1949 DELLVILLE 1949 DELLVILLE NO 1 1949 DELLVILLE NO 1 1949 SMITHFIELD 1949 (Az. mk.)	13 13

C. H. Semper

Book B 7242		-
	1906	<del></del>
ISOLATED BENCH MARKS (C. H. Semper, 1906; Book B 7242; F. K. Swearingen, 1926; Book B 249 R. J. Clinite, 1928; Book B 2863)	8;	<u>Feet</u>
Bagdad, 115 ft WNW. of, and across street from corner of Louisville and Nashville Railroad b car station; 44 ft SW. of SE. rail of main tron iron post; standard cap stamped "912" (Tiennes, 1950)	OX ack•	911.606
Christianburg, 135 ft E. of RR. station; in NE. of front yard at residence of Mrs. Mirian Haliron post; standard cap stamped "903"	corner l; on	903.059
Christianburg, 2.2 mi SW. of, along L. & N. RR. Mulberry Crossing; 44 ft S. and 172 ft E. of a line of rd. crossing RR.; 3 ft W. of fenceling iron post; standard cap stamped "849" (Tied NGS, 1950)	center-	849.155
Sulphur, 3.5 mi SE. of; in corner of field on liwith junction of T-rd. N.; in concrete post; tablet stamped "TT STA NO 24 T 1926" (Reported destroyed, 1954)	ine standard ed	908.655
New Castle, 3.5 mi NE. of; 20 ft SE. of centerly State Highway 193 at junction of T-rd. SE.; in corner of pasture; in concrete post; standard stamped "TT STA NO 22 T 1926" (Reported not 1953)	n NE. tablet	857.298
Delville, 1.1 mi SW. of; 1.0 mi NE. of Mount Gio School; 10 ft S. and 40 ft W. of centerline of at junction of rd. NW.; in corner of field; 4 from walnut tree; in concrete post; standard stamped "TT STA NO 21 T 1926" (Reported destr 1953)	frd. ft tablet	777.643
Franklinton, 2.1 mi SE. of; 3 ft E. of junction known as "Club Lane"; in SE. part of field; in concrete post; standard tablet stamped "TT STA NO 19 T 1926" (Reported not found, 19	<b>ו</b>	882.432
Gratz, 4.0 mi SW. of; 20 ft N. and 20 ft W. of of line of rd. at junction of rd. N.; in corner of field; in concrete post; standard tablet stamp "TT STA NO 18 T 1926" (Reported not found, 19	of oed	817.217

### NEW CASTLE

# 187 KENTUCKY

ISOLATED BENCH MARKS (Cont'd.)	Feet
Eminence, 1.3 mi SW. of; 36 ft N. and 20 ft W. of L. & N. RR. crossing; on RR. property; in concrete post; standard tablet stamped "TT STA NO 29 T 1926" (Tied by NGS, 1935)	
	917.121
Bellview, 180 ft W. of; 28 ft S. of S. rail of L. & N. RR.; on RR. property; in concrete post; standard tablet stamped "TT STA NO 28 T 1926" (Tied by NGS, 1935)	890.746
Defoe, 0.7 mi NW. of; 12 ft N. and 20 ft W. of center-	0,00,140
line of rd. at junction of T-rd. SE.; in corner of pasture; in concrete post; standard tablet stamped "TT STA NO 26 T 1926"	868.925
New Castle; on N. side of entrance to Henry County	
Courthouse; in stone floor of portico; standard tablet stamped "C 1 1928" (Reported destroyed,	
1953)	845.819
Slabtown, 2.2 mi S. of; at Salem School; in E. face of SE. corner of concrete foundation; standard tablet stamped "C 2 1928" (Reported destroyed, 1953)	488.246
LINE 1.	
F. Ludke, 1950; Book AV 190	
New Castle, 4.0 mi NW. of, along U. S. Highway 421; 20 ft N. and 20 ft W. of centerline of hwy. at junction of third-class rd. W.; 9 ft N. of fence corner; in SE. corner of field; in concrete post; standard tablet stamped "TT STA NO 23 T 1926 835"	835.617
U.E., New Castle, 2.6 mi N. of; on NW. concrete guard-	32
wall of bridge over small creek; chiseled square	876.33
Port Royal, 6.8 mi SW. of, along State Highway 193; 31 ft SE. of junction of hwy. and graveled T-rd.; 29 ft E. of centerline of hwy.; 2 ft W. of fenceline; in concrete post; standard tablet stamped "58 FL 1950 858 TT"	0=0
	858.125
Reference mark; 130 ft S. of tablet; 20 ft E. of centerline of State Highway 193; on E. concrete culvert; chiseled square	856.87

101 111111100111	
LINE 1 (Cont'd.)	<u>Feet</u>
U.E., Port Royal, 5.6 mi SW. of; on SE. concrete quardwall of bridge over small creek; chiseled square	781.96
LINE 2.	•
F. Ludke, 1950; Book AV 190	
Franklinton, 1.7 mi NW. of; 40 ft N. and 10 ft E. of centerline of rd. at junction of rd. E.; in corner of pasture; in concrete post; standard tablet stamped "TT STA NO 20 T 1926 766"	765 <b>.</b> 542
Franklinton, 3.0 mi N. of; 45 ft N. and 27 ft E. of centerline of hwy. at junction of graveled rd. E.; 3 ft W. of light pole; in concrete post; standard tablet stamped "46 FL 1950 847"	847.014
LINE 3.	
R. H. Paine, 1952; Book AV 322	
Smithfield, 2.2 mi S. of; 0.3 mi NE. of station; at intersection of State Highways 322 and 22; 130 ft E. of centerline of Highway 322; 27 ft N. of centerline of Highway 22; 4 ft W. of white witness post; 1 ft S. of fenceline; in concrete post; NGS standard azimuth mark disk stamped "SMITHFIELD 1949"	850.107
/Jogs into La Grange quadrangle/	
Shelbyville, 4.0 mi NW. of, along State Highway 53; 400 ft N. of N. end of concrete bridge over Fox Run; 20 ft N. and 50 ft W. of centerline of hwy. at junction of T-rd. NE.; 6 ft NE. of 28-in. locust tree; in S. corner of triangular field; in concrete post; standard tablet stamped "TT STA NO 2 T 1926 735"	734.743
Reference mark; 400 ft S. of tablet; on W. end of N. concrete abutment of bridge over Fox Run Creek; chiseled square	727.86

R. H. Paine

1952

	1952
LINE 4.	Feet
R. H. Paine, 1952; Book AV 322	
New Castle, 3.2 mi W. of, along State Highway 146; 10 ft S. and 125 ft E. of centerline of Highway 146 at junction of Y-rd.; in SE. wingwall of concrete bridge; standard tablet stamped "41 RHP 1952 817"	816.582
U.E., New Castle, 4.3 mi W. of, along State Highway at concrete bridge over Bartlett Fork Creek; on Send of NE. wheelguard; chiseled square	7 146; SE. 793.31
LINE 5.	
R. H. Paine, 1952; Book AV 322	
Eminence; at SE. entrance of L. & N. RR station; in	l 
SW. end of concrete step; NGS standard disk stamped "EMINENCE 1935"	938.643
U.E., Eminence, 0.6 mi N. of; on N. end of E. concrete headwall of culvert; chiseled square	898.99
U.E., Eminence, 1.3 mi N. of; on S. end of E. concrete headwall of culvert; chiseled square	848.26
U.E., Eminence, 2.1 mi N. of; at concrete bridge over Town Creek; on NW. wheelguard; chiseled squa	re 818.20
Eminence, 2.4 mi N. of, along State Highway 55; 2.2 mi S. of New Castle; at concrete bridge over Town Creek; in W. end of N. concrete abutment; standar	
tablet stamped "63 RHP 1952 809"	808.726
Reference mark; 104 ft SE. of tablet; on E. end of abutment; chiseled square	s. 808.67
U.E., New Castle, O.7 mi S. of; on NE. concrete abument of steel bridge over Town Creek; chiseled square	t- 762.86
New Castle; at Henry County Courthouse; in SW. corn of bottom step; standard tablet stamped "64 RHP 1952 844"	,
	•

# 187 KENTUCKY

NEW CASTLE

LINE 5 (Cont'd.)	Feet
Reference mark; 43 ft S. of tablet; in SW. corner of courthouse yard; on W. corner of stone base for memorial; chiseled cross	843.02
U.E., New Castle, 1.0 mi N. of; on NE. concrete wing- wall of bridge; chiseled square	796.40
U.E., New Castle, 1.7 mi N. of; on S. end of E. concrete headwall of culvert; chiseled square	843.47
New Castle, 2.3 mi N. of, along U. S. Highway 421; in large grass triangle formed by junction of Highway 421 and State Highway 193; 88 ft NW. of SW. point of triangle; 75 ft SE. of W. point of triangle; 51 ft SW. of NE. point of triangle; in concrete post; standard tablet stamped	
"TT 8 HF 1951 903"	902.148
U.E., New Castle, 2.5 mi N. of; on NW. concrete wheelguard of bridge over Drennon Creek; chiseled square	976 67
-	876.67
"TT STA NO 23 T 1926 835" (Described in line 1)	835.617
Reference mark; 220 ft N. of tablet; on S. end of E. concrete wheelguard of bridge; chiseled square	836.12
LINE 6.	
R. H. Paine, 1952; Book AV 322	
Reference mark NO. 1; 2.0 mi SE. of Campbellsburg; on property of Leo Bryant; 86 ft SW. of station; 60 ft SE. of powerline pole; 28 ft E. of centerline of State Highway 55; 1 ft E. of fenceline; NGS standard reference mark disk stamped "CAMPBELL NO 1 1949"	918.13
Reference mark No. 2; 2.5 mi SE. of Campbellsburg; on property of Leo Bryant; 104 ft N. of station; 29 ft E. of centerline of State Highway 55; 1 ft E. of fenceline; NGS standard reference mark disk stamped "CAMPBELL NO 2 1949"	916.04

# 187 KENTUCKY

LINE 6 (Cont'd.)	Feet
U.E., New Castle, 4.4 mi N. of; on N. end of W. concrete headwall; chiseled square	887.60
Reference mark; chiseled square (Described in line 3)	836.12
"TT STA NO 23 T 1926 835" (Described in line 1) (Also in line 5)	835.617
LINE 7.	
R. H. Paine, 1952; Book AV 321	
North Pleasureville, 27 ft W. of centerline of rd.; in NE. corner of yard at Presbyterian Church; in concrete post; standard tablet stamped "TT STA NO 27 T 1926 893"	892.695
Reference mark; 560 ft N. of tablet; on N. side of crossroads; on concrete headwall; chiseled square	902.33
North Pleasureville, 0.5 mi W. of, along U. S. Highway 421, thence 2.3 mi N.; 700 ft E. of site of old Willis School; in SW. angle of junction of Y-rd.; 25 ft NW. of junction of rd. SW.; 16 ft S. of junction of rd. W.; 3 ft SW. of corner fence post; in concrete post; standard tablet stamped "66 RHP 1952 813"	812.682
Bethlehem, 0.4 mi SW. of, along State Highway 22; 1.7 mi E. of Point Pleasant Church, along State Highway 573; 230 ft NW. of, and 15 ft lower than junction of Highways 22 and 573; 110 ft SE. of centerline of State Highway 573 at junction of graveled rd. SW.; in NE. concrete headwall of culvert; standard tablet stamped "67 RHP 1952 835"	835.050
Bethlehem, 2.1 mi W. of; 115 ft WNW. of, and 5 ft higher than crossroads; 20 ft N. of centerline of State Highway 573; 16 ft S. of front door of Point Pleasant Christian Church; in second from bottom concrete step; standard tablet stamped "68 RHP 1952 800"	799.717

LINE 7 (Cont'd.)	Feet
Franklinton, 2.4 mi SW. of; 2.0 mi NE. of Point Pleasant Church; 28 ft N. of, and 3 ft higher than centerline of rd. at junction of Y-rd.; 22 ft NW. of centerline of rd.; 25 ft NE. of centerline of graveled rd. NW.; 5 ft N. of corner fencepost; in concrete post; standard tablet stamped "69 RHP 1952 711"	710.601
U.E., Franklinton, 1.6 mi SW. of; on NW. concrete wingwall of bridge over Five Mile Creek; chiseled square	
Franklinton; 400 ft SW. of crossroads; 105 ft SE. of centerline of rd.; 2 ft N. of NW. corner of Baptist Church; in concrete post; standard tablet stamped "70 RHP 1952 868"	653.21 868.129
U.E., Franklinton, 0.6 mi N. of; on SE. end of E. concrete headwall of culvert; chiseled square	816.93
"TT STA NO 20 T 1926 766" (Described in line 2)	765.542
LINE 8.	
R. H. Paine, 1952; Book AV 322	
Eminence, 4.0 mi S. of, along State Highway 55, thence 2.5 mi W.; 196 ft N. of centerline of rd.; 76 ft E. of centerline of driveway; 12 ft W. of fenceline; 11 ft W. of white witness post; in concrete post; NGS standard triangulation station disk stamped "GILTNER 1935"	862.308
Reference mark NO. 1; 164 ft SW. of station; 30 ft NE. of centerline of rd.; 9 ft W. of gatepost; in concrete post; NGS standard reference mark disk stamped "GILTNER NO 1 1935"	861.021
Reference mark NO. 2; 154 ft NW. of station; 64 ft W. of centerline of driveway; 1 ft E. of fenceline; in concrete post; NGS standard reference mark disk stamped "GILTNER NO 2 1935"	857.292

LINE 8 (Cont'd.)	Feet
Eminence, 4.0 mi S. of, along State Highway 55, thence 2.4 mi W.; 28 ft SW. of centerline of rd.; 0.1 mi SE. of station; 68 ft NE. of SE. corner of brick house; 19 ft E. of 24-in. oak tree; in concrete post; NGS standard azimuth mark disk stamped "GILTNER 1935"	854.608
Eminence, 4.0 mi S. of, along State Highway 55; O.1 mi S. of Rogers Grocery; 20 ft S. and 37 ft E. of centerline of State Highway 55 at junction of graveled rd. E.; 4 ft W. of corner fencepost; in concrete post; standard tablet stamped "71 RHP 1952 850"	849.845
Reference mark; 59 ft NW. of tablet; in centerline of State Highway 55 at offset graveled crossroads; rail spike	849.03
Cropper, 2.2 mi W. of; 29 ft S. and 22 ft W. of center- line of crossroads; 3 ft SW. of corner fencepost; in concrete post; standard tablet stamped "72 RHP 1952 796"	795.746
Reference mark; 31 ft NE. of tablet; in centerline of crossroads; rail spike	797.12
"T 31 1934" (NGS)	900.083
LINE 9.	
R. H. Paine, 1952; Book AV 322	
U.E., Jacksonville; 50 ft NE. of, and 1 ft lower than centerline of rd. at junction of T-rd. N.; at Sudduths Grocery; on SW. corner of concrete base for gasoline pumps; chiseled square	911.04
Jacksonville, 1.0 mi N. of; 45 ft S. of, and 4 ft higher than centerline of rd. at junction of T-rd. W.; in concrete post; standard tablet stamped "86 RHP 1952 895"	894.504
Reference mark; 50 ft E. of tablet; in root on NE. side of 60-in. white oak tree; copper nail and washer	888.85

LINE 9 (Cont'd.)	Feet
Jacksonville, 3.4 mi N. of; 25 ft S. and 15 ft W. of, and 1 ft higher than centerline of rd. at junction of Y-rd.; 5 ft S. and 1 ft E. of N. end of plank fence; in concrete post; standard tablet stamped "87 RHP 1952 851"	850.501
Reference mark; 57 ft NE. of tablet; in root on NW. side of 16-in. hickory tree; copper nail and washer	850.45
/Jogs into Lockport quadrangle/	0,00
U.E., Defoe, 3.2 mi NE. of; on W. end of S. concrete headwall of culvert; chiseled square	700.93
U.E., Defoe, 2.1 mi NE. of; on NW. end of NE. corner of concrete headwall of culvert; chiseled square	841.30
Defoe, 1.8 mi NE. of, along U. S. Highway 421; 20 ft S. and 20 ft E. of centerline of hwy. at junction of private rd. S. through gate; in concrete post; standard tablet stamped "TT STA NO 25 T 1926 830"	830.057
Defoe, 1.7 mi NE. of, along U. S. Highway 421; 39 ft N. and 125 ft E. of centerline of Highway 421 at junction of T-rd. N.; 100 ft S. of SE. corner of large barn; 6 ft N. of fence corner; 5 ft NW. of white witness post; in concrete post; NGS standard triangulation station disk stamped "DEFOE 1949"	857.303
Reference mark NO. 1; 53 ft NE. of station; 1 ft NW. of fenceline; in concrete post; NGS standard reference mark disk stamped "DEFOE NO 1 1949"	859.14
Reference mark NO. 2; 49 ft NW. of station; 42 ft NE. of centerline of hwy.; 3 ft NE. of fenceline; in concrete post; NGS standard reference mark disk stamped "DEFOE NO 2 1949"	857.10
Defoe, 1.1 mi E. of, along U. S. Highway 421, thence 1.2 mi N.; 37 ft SE. of, and 4 ft higher than centerline of graveled rd.; 2 ft N. of N. corner of Union Baptist Church; in concrete post; standard tablet stamped "89 RHP 1952 815"	814.610

LINE 9 (Cont'd.)	Feet
Slabtown, 4.6 mi S. of; 1.3 mi N. of Union Baptist Church; 20 ft N. of, and in line with centerline of rd. at junction of rd. S.; 9 ft NE. of 24-in. elm tree; in concrete post; standard tablet stamped "90 RHP 1952 532"	531.904
Reference mark; 8 ft SW. of tablet; in root on NE. side of 24-in. elm tree; copper nail and washer	531.43
Slabtown, 2.0 mi S. of; 3.9 mi N. of Union Baptist Church; 18 ft E. of centerline of rd.; 60 ft N. of drain crossing; 2 ft W. of SW. corner of old Salem School; in concrete post; standard tablet stamped "91 RHP 1952 489"	489.509
Slabtown, 5.9 mi N. of Union Baptist Church; 18 ft NE. of, and 4 ft higher than junction of Y-rd. in line with rd. SW.; 1 ft SW. of fence; in concrete post; standard tablet stamped "92 RHP 1952 480"	480.906
$\sqrt{J}$ ogs into Lockport quadrangle $\sqrt{J}$	
Gratz, 2.5 mi SW. of, along State Highway 22, thence 2.7 mi NW.; 6 ft N. and 13 ft W. of centerline of rd. at curve and junction of T-rd. S.; 25 ft N. of drain crossing; in concrete post; standard tablet stamped "TT 2 TWC 1952 492"	492.922
Reference mark; 45 ft E. of tablet; in root of 16-in. elm tree; rail spike	492.88
Franklinton, 1.7 mi NW. of, thence 1.5 mi W.; 35 ft W. of center of wooden bridge; 12 ft E. of 28-in. hackberry tree; 2 ft S. of wire fence; in concrete post; standard tablet stamped "TT 1 TWC 1952 545"	545.211
Reference mark; 14 ft W. of tablet; in base of 28-in. haw tree; rail spike	545.80
"TT 20 T 1926 766" (Described in line 2)(Also in line 7)	765.542
Delville, 38 ft S. and 52 ft W. of centerline of State Highway 202 at junction of T-rd. SE.; 7 ft N. of 20-in. elm tree; in concrete post; standard tablet stamped "93 RHP 1952 542"	541.434

### 187 KENTUCKY

10) 123110011	
LINE 9 (Cont'd.)	Feet
Reference mark; 63 ft NE. of tablet; in centerline of State Highway 202 at junction of T-rd. SE.; rail spike	541.65
Delville, 1.8 mi SW. of; 0.5 mi NE. of station; 32 ft NW. of centerline of State Highway 202; 2 ft SW. of white witness post; 2 ft S. of corner fence post; in concrete post; NGS standard azimuth mark disk stamped "DELLVILLE 1949"	849.068
Delville, 2.3 mi SW. of, along State Highway 202; opposite Mount Gilead Methodist Church; 38 ft S. of centerline of hwy.; 12 ft S. of fenceline and white witness post; in concrete post; NGS standard triangulation station disk stamped "DELLVILLE 1949"	845.259
Reference mark NO. 1; 110 ft NE. of station; 35 ft S. of centerline of State Highway 202; 2 ft SE. of fenceline; in concrete post; NGS standard reference mark disk stamped "DELLVILLE NO 1 1949"	847.90
Reference mark NO. 2; 115 ft S. of station; 12 ft E. of centerline of graveled rd.; 17 ft S. of power pole; in concrete post; NGS standard reference mark disk stamped "DELLVILLE NO 2 1949"	842.86
"58 FL 1950 858 TT" (Described in line 1)	858.125
Reference mark; chiseled square (Described in line 1)	856.87
"TT 8 HF 1951 903" (Described in line 5)	902.148
LINE 10.	. •
R. H. Paine, 1952; Book AV 322	
"90 RHP 1952 532" (Described in line 9)	531.904
Reference mark; copper nail and washer (Described in line 9)	531.43
LINE 11.	
W. S. Monk, 1952; Book AV 334	
"G 146 1949" (NGS)	886.422
•	

1-10-97

NEW CASTLE QUADRANGLE 187 - KENTUCKY

EMINENCE, 4.0 MI SOUTH OF, ALONG HWY 55; 7.5 MI NORTH OF SHELBYVILLE, ALONG HWY 55; 113 FT EAST AND 52 FT NORTH OF INTERSECTION OF HWY 55 AND STONEY POINT ROAD; 49 FT SW OF SW COR OF A TWO STORY HOUSE; 27 FT EAST OF ROCK WALL; IN CONCRETE POST, FLUSH WITH GROUND; STANDARD TABLET STAMPED "71 RHP 1952 RESET 1996"

RESET ELEVATION 853.475 FT 260.140 M

RESET BY KENTUCKY DEPARTMENT OF TRANSPORTATION FRANKFORT, KENTUCKY DECEMBER 27, 1996

1-10-97

NEW CASTLE QUADRANGLE 187 - KENTUCKY

EMINENCE, 2.2 MI NORTH OF, ALONG STATE HWY 55; 2.2 MI SOUTH OF NEW CASTLE; IN WEST END OF NORTH ABUTMENT OF BRIDGE OVER TOWN CREEK; STANDARD TABLET STAMPED "63 RHP 1952 RESET 1994"

RESET ELEVATION 808.876 FT 246.546 M

RESET BY KENTUCKY DEPARTMENT OF TRANSPORTATION FRANKFORT, KENTUCKY JULY 8, 1994

HORIZONTAL CONTROL NORTH AMERICAN DATUM OF 1927

# UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

38-085-21
NEW CASTLE QUADRANGLE
187 KENTUCKY
N3815-W8500/15
DIAGRAM NJ 16-6
LOUISVILLE

Henry and Shelby Counties

Edition of 5/18/77

LA GRANGE


(188)

PR: CRV/rmm

Plane coordinates are based on Lambert projection, Kentucky, North Zone

Only the permanent marks are listed for control classified obsolete and are not shown on sketch

CARROLLTON (201)



LOCKPORT (186)

MOUNT EDEN

38°15'

INI EDEN (170)

#### DISCLAIMER

We no longer attest to the validity of the positions listed for horizontal control established by transit traverse procedures. This control is now considered <u>OBSOLETE</u> and is included in this list for the purpose of identification only.

₩ 31 1934

### INDEX OF PERMANENT MARKS

7

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11

LONGITUDE 0 1 11

The following positions are considered OBSOLETE. To be used only to locate permanent marks in the field.

By C. A. Turner, 1926; Books C7771, C7766

Gratz, 4.0 mi SW. of; 20 ft N. and 20 ft W. of centerline of rd. at junction of rd. N.; in corner of field; in concrete post; standard tablet stamped "TT STA NO 18 T 1926" (Not found, 1953)

X = 1.784.588

Y = 346.041

38 26 52.23

85 00 07.73

Frnklinton, 2.1 mi SE. of; 3 ft E. of junction of rd. known as "Club Lane"; in SE. part of field; in concrete post; standard tablet stamped "IT STA NO 19 I 1926" (Not found, 1953)

X = 1,774,096

Y = 340.756

38 25 59.12

85 02 19.02

Delville, 1.1 mi SW. of; 1.0 mi NE. of Mount Gilead School; 10 ft S. and 40 ft W. of centerline of rd. at junction of rd. NW.; in corner of field; 4 ft from walnut tree; in concrete post; standard tablet stamped "TI STA NO 21 I 1926" (Reported destroyed, 1953)

X = 1.752.045 Y = 355.358

38 28 21.50

85 06 57.87

New Castle, 3.5 mi NE. of; 20 ft SE. of centerline of State Highway 193 at junction of I-rd. SE.; in NE. corner of pasture; in concrete post; standard tablet stamped "TT STA NO 22 T 1926" (Not found, 1953)

X = 1.741.497 Y = 359.363

38 29 00.09

85 09 11.00

Sulphur, 3.5 mi SE. of; on line with junction of I-rd. N.; in corner of field; in concrete post; standard tablet stamped "TT STA NO 24 T 1926" (Reported destroyed, 1954)

X = 1,719,046

Y = 348.394

38 27 09.39

85 13 51.85

Defoe, 0.7 mi NW. of; 12 ft N. and 20 ft W. of centerline of rd. at junction of T-rd. SE.; in corner of pasture; in concrete post; standard tablet stamped "IT STA NO 26 I 1926"

X = 1.766.370

Y = 310.454

38 20 58.91

85 03 52.76

Bellview; 180 ft W. of Louisville and Nashville Railroad station; 28 ft S. of S. rail; on RR. property; in concrete post; standard tablet stamped "TT STA NO 28 T 1926"

X = 1.743.564

Y = 313.031

38 21 22.29

85 08 39.36

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE

LONGITUDE

#### OBSOLETE MARKS (Cont'd.)

By H. P. Finch, 1951; and C. A. Turner, 1926; Book AH 216

New Castle, 4.0 mi NW. of, along U.S. Highway 421; 20 ft N. and 20 ft W. of centerline of hwy. at junction of third-class rd. W.; 9 ft N. of fence corner; in SE. corner of field; in concrete post; standard tablet stamped "TT STA NO 23 I 1926 835"

X = 1,733,342 Y = 360,215

38 29 07.71

85 10 53.66

New Castle, 2.3 mi N. of, along U.S. Highway 421; in large grassy triangle formed by junction of Highway 421 and State Highway 193; 88 ft NW. of SW. point of triangle; 75 ft SE. of W. point of triangle; 51 ft SW. of NE. point of triangle; in concrete post; standard tablet stamped "IT 8 HF 1951 903"

X = 1,738,082 Y = 353,076

38 27 57.61

85 09 53.17

Port Royal, 6.8 mi SW. of, along State Highway 193; 31 ft SE. of junction of hwy. at graveled I-rd.; 29 ft E. of centerline of hwy.; 2 ft W. of fenceline; in concrete post; standard tablet stamped "58 FL 1950 858 IT"

X = 1,741,513 Y = 359,361

38 29 00.07

85 09 10-79

By T. W. Cayce, 1952; and J. R. Ellis, 1904; Book AH 302

Franklinton, 1.7 mi NW. of; 40 ft N. and 10 ft E. of centerline of rd. at junction of rd. E.; in corner of pasture; in concrete post; standard tablet stamped "TT STA NO 20 T 1926 766"

X = 1.766.412 Y = 356.361

38 28 32.72

85 03 57.34

Franklinton, 1.7 mi NW. of, thence 1.5 mi E.; 35 ft W. of center of wooden bridge; 12 ft E. of 28-in. hackberry tree; 2 ft S. of wire fence; in concrete post; standard tablet stamped "TT 1 TWC 1952 545"

X = 1,773,965 Y = 357,645

38 28 46.06

85 02 22.51

Slabtown, 2.0 mi S. of; 3.9 mi N. of Union Baptist Church; 18 ft E. of centerline of rd.; 60 ft N. of drain crossing; 2 ft W. of SW. corner of old Salem School; in concrete post; standard tablet stamped "91 RHP 1952 489 TT"

X = 1,781,330 Y = 331,264

38 24 25.90

85 00 47.14

Gratz, 2.5 mi SW. of, along State Highway 22, thence 2.7 mi NW.; 6 ft N. and 13 ft W. of centerline of rd. at curve and junction of I-rd. S.; 25 ft N. of drain crossing; in concrete post; standard tablet stamped "TT 2 IWC 1952 492"

X = 1,778,407 Y = 357,101

38 28 41.06

85 01°26,59

STATION

DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11 LONGITUDE 0 1 11

#### OBSOLETE MARKS (Cont'd.)

Slabtown; 5.9 mi N. of Union Baptist Church; 18 ft NE. of, and 4 ft higher than junction of Y-rd. on line with rd. SW.; 1 ft SW. of fence; in concrete post; standard tablet stamped "92 RHP 1952 480 TT"

X = 1.783.943

Y = 340.305

38 25 55.48

85 00 15.24

Slabtown, 4.6 mi S. of; 1.3 mi N. of Union Baptist Church; 20 ft N. of, and in line with centerline of rd. at junction of rd. S.; 9 ft NE. of 24-in. elm tree; in concrete post; standard tablet stamped "90 RHP 1952 532 TT"

X = 1,781,727 Y = 320,219

38 22 36.75

85 00 41.01

Defoe, 1.1 mi E. of, along U. S. Highway 421, thence 1.2 mi N.; 37 ft SE. of, and 4 ft higher than centerline of graveled rd.; 2 ft N. of N. corner of Union Baptist Church; in concrete post; standard tablet stamped "89 RHP 1952 815 TT"

X = 1,777,357 Y = 315,476

38 21 49.50

85 01 35.38

Defoe, 1.8 mi NE. of, along U. S. Highway 421; 20 ft S. and 20 ft E. of centerline of hwy. at junction of private rd. S. through gate; in concrete post; standard tollet stamped "TI SIA NO 25 I 1926 870"

X = 1.777.783

Y = 310.480

38 21 00.15

85 01 29.50

Jacksonville, 3.4 mi M. of; 25 ft S. and 15 ft W. of, and 1 ft higher than centerline of rd. at junction of Y-rd.: 5 ft S. and 1 ft E. of N. end of plank fence; in concrete post; standard tablet stamped "87 RHP 1952 851 TT"

X = 1.783.976

Y = 299.669

38 19 13.78

85 00 10.65

Jacksonville, 1.0 mi N. of: 45 ft S. of, and 4 ft higher than centerline of rd. at junction of I-rd. W.: in concrete post: standard tablet stamped "86 RHP 1952 895 IT"

X = 1.780.725

Y = 288,153

38 17 19.67

85 00 50.25

By T. W. Cayce, 1952; and C. A. Turner, 1926; Book AN 302

Franklinton; 400 ft SW. of crossroads; 105 ft SE. of centerline of graveled rd.; 2 ft N. of NW. corner of Baptist Church; in concrete post; standard tablet stamped "70 RHP 1952 868 IT"

X = 1.768.858

Y = 347.333

38 27 03.69

85 03 25,60

STATION DESCRIPTION PLANE COORDINATES. FEET

LATITUDE

LONGITUDE 0 11 11

#### OBSOLETE MARKS (Cont'd.)

Franklinton, 2.4 mi SW. of; 2.0 mi NE. of Point Pleasant Christian Church; 28 ft N. of, and 3 ft higher than centerline of rd. at junction of Y-rd.; 25 ft NE. of centerline of graveled rd. NW.; 22 ft NW. of centerline of graveled rd.: 5 ft N. of fence corner; in concrete post; standard tablet stamped "69 RHP 1952 711 71"

X = 1.759.762

Y = 341.098

38 26 01.25

85 05 19.22

Bethlehem, 2.1 mi W. of; 115 ft WNW. of, and 5 ft higher than crossroads; 20 ft N. of centerline of State Highway 573; 16 ft S. of front door of Point Pleasant Christian Church; in second from bottom concrete step; standard tablet stamped "68 RHP 1952 800 TT"

X = 1,755,041 Y = 332.036

38 24 31.24

85 06 17.47

Bethlemhem, 0.4 mi SW. of, along State Highway 22; 1.7 mi E. of Point Pleasant Christian Church along State Highway 573; 230 ft NW. of, and 15 ft lower than junction of Highways 22 and 573; 110 ft SE. of centerline of Highway 573 at junction of graveled rd. SW.; in NE. concrete headwall of culvert: standard tablet stamped "67 RHP 1952 835 TT"

X = 1,762,927

Y = 328.636

38 23 58.34

85 04 38.04

By T. W. Cayce, 1952; Book AH 302

North Pleasureville, 0.5 mi W. of, along U. S. Highway 421, thence 2.3 mi N.; 700 ft E. of site of old Willis School; in SW. angle of junction of Y-rd.; 25 ft NW. of junction of rd. SW.; 16 ft S. of junction of rd. W.; 3 ft SW. of corner fencepost; in concrete post; standard tablet stamped "66 RHP 1952 813 TI"

X = 1.754.044 Y = 322.094

38 22 52.87

85 06 28.84

North Pleasureville; in NE. corner of Presbyterian Churchyard; 27 ft W. of centerline of rd.; in concrete post; standard tablet stamped "IT STA NO 27 T 1926 893"

X = 1.753.884

Y = 313.659

38 21 29.47

85 06 29.87

Pleasureville, 1.1 mi SW. of, along State Highway 241; 10 ft S. and 30 ft E. of driveway crossing; 1 ft W. of wire fence at gate entrance to farm; in concrete post; standard tablet stamped "TT 9 TWC 1952"

X = 1.748.255

Y = 304.598

38 19 59.38

85 07 39.46

Cropper: 500 ft W. of post office, along State Highway 43 to junction with State Highway 241; 17 ft S. of hwy. junction sign; 2 ft W. of guardrail; in concrete post; standard tablet stamped "TT 10 TWC 1952"

X = 1.751.441 Y = 296.830

38 18 42.89

85 06 58,55

STATION .

20

N DESCRIPTION PLANE COORDINATES, FEET

LATITUDE . "

LONGITUDE

#### OBSOLETE MARKS (Cont'd.)

By T. W. Cayce, 1952; and C. B. Kendall, 1905; Book AH 302

Cropper, 1.5 mi S. of, along State Highway 43, thence 0.7 mi SE. along paved rd.; 77 ft N. and 70 ft E. of centerline of rd. at junction of I-rd. N.; 1 ft S. of wire fence; in concrete post; standard tablet stamped "IT 11 TWC 1952"

X = 1.752.979

Y = 288.370

38 17 19.40

85 06 38.27

Christianburg; 60 ft S. of S. corner of L. & N. RR. station; 28 ft W. of mailbag support; 14 ft SW. of SW. rail; in concrete post; NGS standard disk stamped "W 31 1934" (Reported disturbed, 1949)

X = 1.756.238

Y = 284.478

38 16 41.22

85 05 56,95

New Castle, 3.2 mi W. of, along State Highway 146; 10 ft S. and 125 ft E. of centerline of Highway 146 at junction of Y-rd.; in SE. concrete wingwall of bridge; standard tablet stamped "41 RHP 1952 817 TT"

X = 1.719.324

Y = 339.673

38 25 43.22

85 13 47.19

By T. W. Cayce, 1952-1953 and C. A. Turner, 1926; Book AH 302

Shelbyville, 4.0 mi NW. of, along State Highway 53; 400 ft N. of N. end of concrete bridge over Fox Fun; 20 ft N. and 50 ft W. of centerline of hwy. at junction of I-rd. NE.; 6 ft NE. of 28-in. locust tree; in S. corner of triangular field; in concrete post; standard tablet stamped "TT STA NO 2 T 1926 735" (Reported destroyed, 1953)

X = 1.714.146

Y = 279.011

38 15 43.01

85 14 44.03

#### MARK TIED BY NGS

By C. A. Turner, 1926; Books C7771, C7766

Eminence, 1.3 mi SW. of; 36 ft N. and 20 ft W. of L. & N. RR. crossing; on RR. property; in concrete post; standard tablet stamped "TT STA NO 29 T 1926"

X = 1.727,201.24 Y = 316.698.07

38 21 56.923

85 12 05.168

QUADRANGLE	KY 18 /
ANOTHER THE STATE STATE OF THE	AND AND ADMINISTRATION OF THE STREET, COMMENTS OF THE STREET,
	GALERTINE MAIN AND AND AND AND AND AND AND AND AND AN
	* A sent determined and account to the desired and the sent and
11/89	

#### FOR HORIZONTAL CONTROL

# COMPUTER PRINT-OUT

SEE BOOK LESSEE BLA

HY HAPPEN PROJECT MANAGEMENT

# COPY SUITABLE FOR XEROX

KY / FF GUAD.

Bels, hold is to be stapled to the inside front bover of the hosizontal control folder.